








Rocker Switches

21x9.5mm Half Body SP Rocker Switches

RK6 Series




RK6S3Q4_ _ _ _N ON-OFF-ON; Without Waterproof Cover



RK6S1Q4_ _ _ _W ON-OFF; With Waterproof Cover

TERMINAL




ACTUATOR


4 Curve
(No Illuminated)



ACTUATOR MARKING




PANEL SIZE



Note: The described Front Panel Mounting Hole is a proposal only and not universally valid. We recommend that customers test the applicability of the Front Panel Mounting Hole with switch samples and define the fitting Front Panel Mounting Hole measurements individually.

How to order:



1 POLES:
S Single Pole

2 SWITCHING:
1 ON - OFF
2 ON - ON
3 ON - OFF - ON

3 TERMINAL (See above drawings):
Q 4.8mm TAB, 0.8mm THICK
D Solder Tag

4 ACTUATOR (See above drawings):
4 Curve

5 ACTUATOR MARKING:
A See above drawings
B See above drawings
C See above drawings
D See above drawings
F See above drawings
G See above drawings

6 BASE COLOR:
A Black
H Grey
B White

7 ACTUATOR COLOR:
A Black
H Grey
B White
C Red

8 WATERPROOF COVER:
N None Cover (Standard)
W With Waterproof Cover

General Specifications:

FEATURES

- » Single pole half body rocker switch up to 10(4)A 250VAC
- » Non-illuminated

MATERIALS

- » Contact Arm: Silver plated copper alloy
- » Terminal: Silver plated copper
- » Spring: Piano wire

MECHANICAL

- » Temperature Range: -20°C to +85°C

ELECTRICAL

- » Electrical Life: 10,000 cycles
- » Rating: 13A125VAC / 10A250VAC / 1/2HP 125/250VAC / 10A125/250VAC / 10(4)A250VAC~ μT85

- » Initial Contact Resistance: 20m Ω max.
- » Insulation Resistance: 100M Ω min. at 500VDC