





# Rocker Switches

## 32x25mm illuminated Rocker Switches



## RK11 Series





RK11D1Q2CTCL\_N



RK11D1Q1CDN\_W



RK11D1Q1CCA\_U\_N



RK11D1Q1FAN\_N

TERMINAL	ACTUATOR SHAPE	ACTUATOR MARKING	PANEL SIZE
	<p><b>ACTUATOR TYPE</b></p> <p>F Flat Actuator (Only for illuminated)</p> <p>C Curve Actuator</p> <p>C Curve Actuator without Len                      CC Curve Actuator with red Len                      CF Curve Actuator with green Len                      CD Curve Actuator with orange Len                      CG Curve Actuator with blue Len</p>	<p>Single Shape:</p> <p>A OFF ON                      B OFF ON                      C O I                      D O -                      F LO HI                      M I O II</p> <p>Twin Shapes:</p> <p>T1                      T2                      TF Green Len                      TC Red Len                      TD Orange Len</p>	<p>PANEL CUT-OUT                      Snap-in mounting</p> <p>Note: The described Front Panel Mounting Hole is a proposal only and not universally valid. We recommend that customers test the applicability of the Front Panel Mounting Hole with switch samples and define the fitting Front Panel Mounting Hole measurements individually.</p>

### How to order:

RK11

- 1 POLES:**  
S Single Pole  
D Double Poles
- 2 SWITCHING:**  
1 ON - OFF  
2 ON - ON  
3 ON - OFF - ON  
4 MOM - OFF  
5 MOM - ON  
7 MOM - OFF - ON  
8 MOM - OFF - MOM
- 3 TERMINAL**  
(See above drawings):  
Q Quick Connect  
D1 Solder Tag Type 1  
D4 Solder Tag Type 4  
S Screw Tag  
P PC Tag
- 4 ACTUATOR SHAPE**  
(See above drawings):  
1 Single  
2 Twin
- 5 ACTUATOR TYPE**  
(See above drawings):  
F C CC CF CD CG
- 6 ACTUATOR MARKING**  
(See above drawings):  
A B C D F M  
T1 T2 TF TC TD
- 7 ILLUMINATION:**  
N No Illuminated  
U Illuminated (Only RK11\_1)  
L Circuit Lens (Only RK11\_1)
- 8 BASE COLOR:**  
A Black H Grey B White
- 9 ACTUATOR COLOR:**  
A Black H Grey B White  
C Red F Green D Orange
- 10 WATERPROOF COVER:**  
N None Cover (Standard)  
W With Waterproof Cover  
P Protection Guard

### General Specifications:

#### FEATURES

- » Rocker switch up to 20A 125VAC
- » Illuminated or non-illuminated

#### MATERIALS

- » Contact: Silver alloy
- » Terminals: Silver plated copper
- » Lamp: Neon for AC; Tungsten bulb for DC
- » Spring: Piano wire

#### MECHANICAL

- » Temperature Range: -20°C to +125°C

#### ELECTRICAL

- » Electrical Life: 10,000 cycles at 16(4)A250VAC  
50,000 cycles at 10(2)A250VAC
- » Rating: 16A125VAC 1/4HP  
16A250VAC1/4HP  
16A250VAC  
20A125VAC3/4HP  
16(4)A250V-T125  
10(2)A250V-T125  
16(8)A250V-T125
- » Initial Contact Resistance: 20m Ω max.
- » Insulation Resistance: 100M Ω min. at 500VDC